



Dry



Wet



Heat



Oily



Cold



Chemical



# TG6240

Conforming to cut level E under the new EN388:2016 standard, TG6240 has unrivalled levels of dexterity and comfort and is designed to last for long periods of time.

The MicroDex ultra coating and new Life Extending Technology makes the TG6240 perfect for high cut risk tasks in wet, dry and oily conditions. Also features a thumb crotch to further extend the wear life of the glove.

## Key Features

- LXT Engineering triple wrapped core for extra cut protection and a soft luxurious feel for the wearer
- Hot contact resistance up to 100°C
- LXT Treatment for water, oil and dirt resistance and reduced staining
- Reinforced thumb crotch for enhanced longevity
- A breathable 15gg liner, making the glove highly dexterous and tactile
- Touchscreen compatible

## Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Oil and Gas
- Rail
- Mechanical and Electrical
- Waste, Recycling and Local Authority

|                |                      |                   |                  |
|----------------|----------------------|-------------------|------------------|
| <b>Sizes:</b>  | 6-11                 | <b>Gauge:</b>     | 15gg             |
| <b>Liner:</b>  | Polyamide/HPPE/Steel | <b>Coating:</b>   | MicroDex Nitrile |
| <b>No/Bag:</b> | 10                   | <b>No/Carton:</b> | 100              |



# TG6240

## Glove Specifications

### Glove lengths

220mm-270mm

### Glove Weight

15 gauge

### Liner Type

Engineered HPPE/Polyamide/Stainless Steel

### Glove colour

Pantone 368c / R:92 G:193 B:81 / C:63 M:0 Y:100 K:0

### Overlock Colours

| SIZE   | XS-6 | S-7 | M-8    | L-9   | XL-10  | 2XL-11 | 3XL-12 |
|--------|------|-----|--------|-------|--------|--------|--------|
| COLOUR | BLUE | RED | ORANGE | WHITE | YELLOW | BLACK  | GREEN  |

## Coating Specifications

### Coating colour

Black

### Dip type

Nitrile Microfoam

### Dip Application

Palm Dipped

### Glove Treatment

Patent pending LXT Treatment



## Packaging Information

### Qty/bag

10 pairs

### Qty/carton

100 pairs

### Carton Dimensions

290mm x 440mm x 280mm

## Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

### Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

### Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.