TRUKKA TT955

Cut Level E Driver's Glove

SPECIFICATION & CHARACTERISTICS

CODE

TT955

SIZE RANGE

8/M - 11/2XL

PACKAGING

10 pairs/pack - 100 pairs/carton

LEATHER

Top grade cow grain leather

LINER

Kevlar

CHARACTERISTICS

- · Outstandingly soft and supple leather
- · Precise fit with four sizes
- Excellent mechanical strength
- Elastic tensioner for snug fit
- · Cut resistant kevlar lining around the palm of the glove to protect the wearers from cut risks.

STANDARDS COMPLIANCE

EN388: 2016 Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

| 2 = Abrasion | (Performance Index 1-4) |
|------------------------|-------------------------|
| X = Blade Cut* (Coup) | (Performance Index 1-5) |
| 3 = Tear | (Performance Index 1-4) |
| 2 = Puncture | (Performance Index 1-4) |
| E = Cut (EN ISO 13997) | (Rating A-F) |

Notes: Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

^{*}Gloves should not be used when working with serrated blades.



